

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous

Products Regulation (February 11, 2015).

Revision Date: 08/28/2018 Date of Issue: 12/19/2014 Version: 2.0

## **SECTION 1: IDENTIFICATION**

#### 1.1. Product Identifier

Product Form: Mixture
Product Name: Nickel Alloys

Synonyms: Common Alloy / Grade: Bar, Sheet, Plate, Tubing, Pipe

# 1.2. Intended Use of the Product

Solid Product, Various Forms and Uses.

#### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Joseph T. Ryerson & Son, Inc. 227 W Monroe St., 27th Floor Chicago, Illinois 60606 T (312) 292-5000

### www.ryerson.com

# 1.4. Emergency Telephone Number

Emergency Number : CHEMTREC (US Transportation): (800) 424-9300 CANUTEC (Canadian Transportation): (613) 996-6666

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC - Day or Night

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the Substance or Mixture

#### **GHS-US/CA Classification**

 Skin Sens. 1
 H317

 Carc. 1B
 H350

 Repr. 2
 H361

Full text of hazard classes and H-statements: see Section 16.

#### 2.2. Label Elements

**GHS-US/CA Labeling** 

Hazard Pictograms (GHS-US/CA)





Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H317 - May cause an allergic skin reaction.

H350 - May cause cancer.

H361 - Suspected of damaging fertility or the unborn child.

Precautionary Statements (GHS-US/CA): P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing fume, dust.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P321 - Specific treatment (see Section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national,

territorial, provincial, and international regulations.

08/28/2018 EN (English US) 1/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

#### 2.3. Other Hazards

This product as shipped is physiologically inert in its solid form. However, user-generated dust and/or fumes may pose a physiological hazard if inhaled or ingested. Avoid inhalation of metal dusts and fumes. May cause an influenza-like illness. Avoid skin and eye contact with dusts to prevent mechanical irritation. User-generated dust is easily ignited and difficult to extinguish.

#### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Nickel	(CAS-No.) 7440-02-0	30 - 99	Skin Sens. 1, H317
			Carc. 2, H351
			STOT RE 1, H372
			Comb. Dust
Iron	(CAS-No.) 7439-89-6	0.1 - 66	Comb. Dust
Chromium	(CAS-No.) 7440-47-3	0.1 - 48	Comb. Dust
Copper	(CAS-No.) 7440-50-8	0.1 - 45	Comb. Dust
Cobalt	(CAS-No.) 7440-48-4	0.1 - 40	Acute Tox. 4 (Oral), H302
			Acute Tox. 1 (Inhalation:dust,mist), H330
			Eye Irrit. 2A, H319
			Resp. Sens. 1B, H334
			Skin Sens. 1, H317
			Carc. 1B, H350
			Repr. 2, H361
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
			Comb. Dust
Molybdenum	(CAS-No.) 7439-98-7	0.1 - 17	Comb. Dust
Aluminum	(CAS-No.) 7429-90-5	0.1 - 13	Comb. Dust
Manganese	(CAS-No.) 7439-96-5	0.1 - 11	Comb. Dust
Niobium	(CAS-No.) 7440-03-1	0.1 - 8	Not classified
Tungsten	(CAS-No.) 7440-33-7	0.1 - 5	Comb. Dust
Titanium	(CAS-No.) 7440-32-6	0.1 - 5	Comb. Dust
Tantalum	(CAS-No.) 7440-25-7	0.1 - 5	Not classified
Silicon	(CAS-No.) 7440-21-3	0.1 - 4	Comb. Dust
Yttrium	(CAS-No.) 7440-65-5	0.1 - 1	Comb. Dust

The above listing is a summary of elements used in alloying nickel. Various grades will contain different combinations of these elements. Other trace elements may also be present in minute amounts. These small quantities (less than 0.1%) are frequently referred to as "trace" or "residual" elements; generally they originate in the raw material used. Such elements include arsenic (As), boron (B),carbon (C), lead (Pb), oil mist (mineral1), oxygen (O), phosphorus (P), sulfur (S), tin (Sn), vanadium (V), and zirconium (Zr). Various byproducts of processing from these trace elements may include nitric oxide, nitrogen dioxide, ozone, and sulfur dioxide, and these byproducts may also be considered trace. If listed in the above table, the ingredient is considered to be a component rather than trace.

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of First-aid Measures

General: If injury occurs or if you feel unwell seek medical advice.

**Inhalation:** If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

08/28/2018 EN (English US) 2/17

<sup>\*</sup>Nickel alloy products as provided contain chromium metal in the zero valence state. As such, chromium metal does not present any unusual health hazard. However, welding, torch cutting, brazing, or grinding of chromium metal present in nickel alloys may generate airborne concentrations of hexavalent chromium. Full text of H-phrases: see Section 16.

<sup>\*</sup>Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Skin Contact:** Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance. Remove contaminated clothing. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Immediately rinse with water for a prolonged period (at least 15 minutes) while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Skin sensitization. May cause cancer. Suspected of damaging the unborn child. Under normal conditions of use not expected to present a significant hazard. Under milling, or physical alteration metal dusts may be produced that cause irritation of the respiratory tract, skin, and may be harmful. Molten material may release toxic, and irritating fumes.

**Inhalation:** During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

**Skin Contact:** Dust may cause irritation in skin folds or by contact in combination with tight clothing. Contact with hot, molten metal will cause thermal burns. Removal of solidified molten material from skin requires medical assistance.

**Eye Contact:** Dust generated from material cutting may cause a slight irritation. Slivers may be generated, which could cause mechanical irritation or injure the eye. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Ingestion: If large amounts are ingested: Gastrointestinal irritation.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Inhalation of iron oxide fumes undergoing decomposition may cause irritation and flu-like symptoms, otherwise iron oxide is not hazardous. Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Copper: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. Molybdenum: Chronic exposure to molybdenum compounds is suspected of causing cancer. Compounds are also known to cause irritation to the skin, eyes, and respiratory tract. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Chronic exposure to excessive manganese levels can lead to a variety of psychiatric and motor disturbances, termed manganism. Repeated exposure to tantalum alloys may cause fibrosis, chronic rhinitis and "hard metal pneumoconiosis". Silicon: Can cause chronic bronchitis and narrowing of the airways.

# 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

# **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use halogenated extinguishing agents on small chips or fines. Do not use water when molten material is involved, contact of hot product with water will result in a violent expansion as the water turns to steam causing explosion with massive force.

# 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but will burn at high temperatures. Small chips, turnings, dust and fines from processing may be readily ignitable.

Explosion Hazard: Product is not explosive. Dust generated from processing may present a dust explosion hazard.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

08/28/2018 EN (English US) 3/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Firefighting Instructions:** Do not breathe fumes from fires or vapors from decomposition. Keep upwind. Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Firefighters must use full bunker gear including NIOSH-approved positive-pressure self-contained breathing apparatus to protect against potential hazardous combustion and decomposition products.

**Hazardous Combustion Products**: Metallic oxides. Nickel oxides. Iron oxides. If heated to the point of fume generation zinc fumes may cause metal fume fever. Otherwise, zinc is non-toxic.

#### **Reference to Other Sections**

Refer to Section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe dust or fumes.

### 6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

#### 6.2. Environmental Precautions

Do not allow to enter drains or water courses.

#### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. Collect scrap for recycling. If molten: contain the flow using dry sand or salt flux as a dam. Do not use shovels or hand tools to halt the flow of molten material. Allow the spill to cool before re-melting as scrap.

**Methods for Cleaning Up:** Avoid generation of dust during clean-up of spills. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up. Use only non-sparking tools. Use explosion-proof equipment.

#### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Risk of thermal burns on contact with molten product. Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations. May be a potential hazard under the following conditions:

- Small chunks, dust or fines in contact with water can generate flammable or toxic gases. These gases could present an explosion hazard in confined or poorly ventilated spaces.
- Molten metal in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide). Moisture entrapped by molten metal can be explosive. Contact of molten aluminum with certain metal oxides can initiate a thermite reaction. Finely divided metals (e.g., powders or wire) may have enough surface oxide to produce thermite reactions/explosions.

**Precautions for Safe Handling:** Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid creating or spreading dust. Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Ensure there is adequate ventilation. Wear recommended personal protective equipment.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke in areas where product is used.

## 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in original container. Store in a dry, cool place. Store in a well-ventilated place. Keep container tightly closed.

**Incompatible Materials:** Oxidizers. Acids. Bases. Mineral acids. Corrosive substances in contact with metals may produce flammable hydrogen gas.

08/28/2018 EN (English US) 4/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

# 7.3. Specific End Use(s)

Solid Product, Various Forms and Uses.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control Parameters

For substances listed in Section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

governments.		
Nickel (7440-02-0)		
USA ACGIH	ACGIH TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Suspected as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.015 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m³)	10 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m³)	1.5 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m³)	0.05 mg/m³
Manitoba	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	1 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	3 mg/m³ (inhalable fraction)
Nunavut	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Northwest Territories	OEL STEL (mg/m³)	3 mg/m³ (inhalable fraction)
Northwest Territories	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Ontario	OEL TWA (mg/m³)	1 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable particulate matter)
Québec	VEMP (mg/m³)	1 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m³)	3 mg/m³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m³)	1.5 mg/m³ (inhalable fraction)
Yukon	OEL STEL (mg/m³)	3 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m³)	1 mg/m <sup>3</sup>
Chromium (7440-47-3)		
USA ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.5 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m³)	250 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m³)	0.5 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m³)	0.5 mg/m³
Manitoba	OEL TWA (mg/m³)	0.5 mg/m³
New Brunswick	OEL TWA (mg/m³)	0.5 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	0.5 mg/m³
Nova Scotia	OEL TWA (mg/m³)	0.5 mg/m³
Nunavut	OEL STEL (mg/m³)	1.5 mg/m³ (metal)
Nunavut	OEL TWA (mg/m³)	0.5 mg/m³ (metal)
Northwest Territories	OEL STEL (mg/m³)	1.5 mg/m³ (metal)
Northwest Territories	OEL TWA (mg/m³)	0.5 mg/m³ (metal)
Ontario	OEL TWA (mg/m³)	0.5 mg/m <sup>3</sup>
Prince Edward Island	OEL TWA (mg/m³)	0.5 mg/m <sup>3</sup>
Québec	VEMP (mg/m³)	0.5 mg/m <sup>3</sup>
Saskatchewan	OEL STEL (mg/m³)	1.5 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m³)	0.5 mg/m <sup>3</sup>

08/28/2018 EN (English US) 5/17

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	. 38 / Monday, March 26, 2012 / Rules And Regulations /	
Yukon	OEL STEL (mg/m³)	3 mg/m³
Yukon	OEL TWA (mg/m³)	0.1 mg/m <sup>3</sup>
Copper (7440-50-8)		
USA ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m³ (fume)
USA OSHA	OSHA PEL (TWA) (mg/m³)	0.1 mg/m³ (fume)
	, ,, ,,	1 mg/m³ (dust and mist)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³ (dust and mist)
	, ,, ,	0.1 mg/m³ (fume)
USA IDLH	US IDLH (mg/m³)	100 mg/m³ (dust, fume and mist)
Alberta	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
		1 mg/m³ (dust and mist)
British Columbia	OEL TWA (mg/m³)	1 mg/m³ (dust and mist)
		0.2 mg/m³ (fume)
Manitoba	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
New Brunswick	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
		1 mg/m³ (dust and mist)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
Nova Scotia	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
Nunavut	OEL STEL (mg/m³)	3 mg/m³ (dust and mist)
		0.6 mg/m³ (fume)
Nunavut	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
		1 mg/m³ (dust and mist)
Northwest Territories	OEL STEL (mg/m³)	3 mg/m³ (dust and mist)
		0.6 mg/m³ (fume)
Northwest Territories	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
		1 mg/m³ (dust and mist)
Ontario	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
		1 mg/m³ (dust and mist)
Prince Edward Island	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
Québec	VEMP (mg/m³)	0.2 mg/m³ (fume)
		1 mg/m³ (dust and mist)
Saskatchewan	OEL STEL (mg/m³)	0.6 mg/m³ (fume)
		3 mg/m³ (dust and mist)
Saskatchewan	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
	2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	1 mg/m³ (dust and mist)
Yukon	OEL STEL (mg/m³)	0.2 mg/m³ (fume)
× 1	051.714/4 / 3)	2 mg/m³ (dust and mist)
Yukon	OEL TWA (mg/m³)	0.2 mg/m³ (fume)
		1 mg/m³ (dust and mist)
Cobalt (7440-48-4)	ACCULTINA / / 2)	0.00 / 3
USA ACGIH	ACGIH TWA (mg/m³)	0.02 mg/m³
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to
LICA ACCIT	Biological Form	Humans
USA ACGIH	Biological Exposure Indices (BEI)	15 μg/l Parameter: Cobalt - Medium: urine - Sampling
LICA OCULA	OCHA DEL (TWA) / 2)	time: end of shift at end of workweek (nonspecific)
USA NIGGU	OSHA PEL (TWA) (mg/m³)	0.1 mg/m³ (dust and fume)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (dust and fume)
USA IDLH	US IDLH (mg/m³)	20 mg/m³ (dust and fume)
Alberta	OEL TWA (mg/m³)	0.02 mg/m³
British Columbia	OEL TWA (mg/m³)	0.02 mg/m³
Manitoba	OEL TWA (mg/m³)	0.02 mg/m³
New Brunswick	OEL TWA (mg/m³)	0.02 mg/m <sup>3</sup>

08/28/2018 EN (English US) 6/17

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

ewfoundland & Labrador         OEL TWA (mg/m³)         0.02 mg/m³           ova Scotia         OEL TWA (mg/m³)         0.02 mg/m³
OFI CTF1 /mm /mm3\
unavut OEL STEL (mg/m³) 0.06 mg/m³
unavut OEL TWA (mg/m³) 0.02 mg/m³
orthwest Territories OEL STEL (mg/m³) 0.06 mg/m³
orthwest Territories OEL TWA (mg/m³) 0.02 mg/m³
ntario OEL TWA (mg/m³) 0.02 mg/m³
rince Edward Island OEL TWA (mg/m³) 0.02 mg/m³
uébec VEMP (mg/m³) 0.02 mg/m³
OEL STEL (mg/m³) 0.06 mg/m³
Askatchewan OEL TWA (mg/m³) 0.02 mg/m³
ukon OEL STEL (mg/m³) 0.15 mg/m³ (dust and fume)
ukon OEL TWA (mg/m³) 0.05 mg/m³ (dust and fume)
lolybdenum (7439-98-7)
Internal TWA (mg/m³) 5 mg/m³ (Molybdenum (as Mo), Soluble Compounds)
SA ACGIH ACGIH TWA (mg/m³) 10 mg/m³ (inhalable particulate matter)
3 mg/m³ (respirable particulate matter)
SA OSHA OSHA PEL (TWA) (mg/m³) 5 mg/m³ (Molybdenum (as Mo), Soluble Compounds)
15 mg/m³ (Molybdenum (as Mo), Insoluble Compounds
(Total dust)
SA NIOSH NIOSH REL (TWA) (mg/m³) 5 mg/m³ (Molybdenum (as Mo), Soluble Compounds)
SA IDLH US IDLH (mg/m³) 5000 mg/m³
lberta OEL TWA (mg/m³) 10 mg/m³ (total)
3 mg/m³ (respirable)
ritish Columbia OEL TWA (mg/m³) 3 mg/m³ (respirable)
10 mg/m³ (inhalable)
lanitoba  OEL TWA (mg/m³)  3 mg/m³ (respirable particulate matter)
10 mg/m³ (inhalable particulate matter)
ewfoundland & Labrador OEL TWA (mg/m³)  3 mg/m³ (respirable particulate matter)
10 mg/m³ (inhalable particulate matter)
ova Scotia  OEL TWA (mg/m³)  3 mg/m³ (respirable particulate matter)
unavut 10 mg/m³ (inhalable particulate matter)  20 mg/m³ (metal-inhalable fraction)
6 mg/m³ (metal-initialable fraction)
unavut OEL TWA (mg/m³) 10 mg/m³ (metal-inhalable fraction)
3 mg/m³ (metal-initialable fraction)
orthwest Territories OEL STEL (mg/m³) 20 mg/m³ (metal-inhalable fraction)
6 mg/m³ (metal-respirable fraction)
orthwest Territories OEL TWA (mg/m³) 10 mg/m³ (metal-inhalable fraction)
3 mg/m³ (metal-respirable fraction)
ntario OEL TWA (mg/m³) 10 mg/m³ (metal-inhalable)
3 mg/m³ (metal-respirable)
rince Edward Island  OEL TWA (mg/m³)  3 mg/m³ (respirable particulate matter)
10 mg/m³ (inhalable particulate matter)
oskatchewan OEL STEL (mg/m³) 20 mg/m³ (inhalable fraction)
6 mg/m³ (respirable fraction)
Askatchewan OEL TWA (mg/m³) 10 mg/m³ (inhalable fraction)
3 mg/m³ (respirable fraction)
luminum (7429-90-5)
SA ACGIH ACGIH TWA (mg/m³) 1 mg/m³ (respirable particulate matter)
( 6,  )
SA ACGIH  ACGIH chemical category  Not Classifiable as a Human Carcinogen  SA OSHA  OSHA PEL (TWA) (mg/m³)  15 mg/m³ (total dust)

08/28/2018 EN (English US) 7/17

		5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
33711113311	11103111122 (11171) (1118) 111 )	5 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	10 mg/m³ (dust)
British Columbia	OEL TWA (mg/m³)	1 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (metal dust)
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (metal-dust)
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (metal-dust)
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (metal-dust)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (metal-dust)
Ontario	OEL TWA (mg/m³)	1 mg/m³ (respirable)
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³ (respirable particulate matter)
Québec	VEMP (mg/m³)	10 mg/m³
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (dust)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (dust)
Manganese (7439-96-5)	1	
USA ACGIH	ACGIH TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
OSA ACGIII	Acdin twa (ing/iii )	0.1 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	5 mg/m³ (fume)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³ (fume)
USA NIOSH	NIOSH REL (STEL) (mg/m³)	3 mg/m³
USA IDLH	US IDLH (mg/m³)	500 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m³)	0.2 mg/m³
British Columbia	OEL TWA (mg/m³)	0.2 mg/m³
Manitoba	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
	0== (8, )	0.1 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	0.2 mg/m <sup>3</sup>
Newfoundland & Labrador	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
	, ,	0.1 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
	,	0.1 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	0.6 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m³)	0.2 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m³)	0.6 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m³)	0.2 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m³)	0.2 mg/m <sup>3</sup>
Prince Edward Island	OEL TWA (mg/m³)	0.02 mg/m³ (respirable particulate matter)
		0.1 mg/m³ (inhalable particulate matter)
Québec	VEMP (mg/m³)	0.2 mg/m³ (total dust and fume)
Saskatchewan	OEL STEL (mg/m³)	0.6 mg/m³
Saskatchewan	OEL TWA (mg/m³)	0.2 mg/m <sup>3</sup>
Yukon	OEL Ceiling (mg/m³)	5 mg/m³
Tungsten (7440-33-7)		
USA ACGIH	ACGIH TWA (mg/m³)	3 mg/m³ (respirable particulate matter)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³
Alberta	OEL STEL (mg/m³)	10 mg/m³
Alberta	OEL TWA (mg/m³)	5 mg/m <sup>3</sup>

08/28/2018 EN (English US) 8/17

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

recording to reactar neglecting to 177, 10	5. 56 / Worlday, Waren 26, 2012 / Rules And Regulations And	According to the nazardous Products Regulation (February 11, 2015).
British Columbia	OEL STEL (mg/m³)	10 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m³)	5 mg/m <sup>3</sup>
Manitoba	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)
Newfoundland & Labrador	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)
Nunavut	OEL STEL (mg/m³)	10 mg/m³
Nunavut	OEL TWA (mg/m³)	5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	10 mg/m³
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³
Ontario	OEL STEL (mg/m³)	10 mg/m³
Ontario	OEL TWA (mg/m³)	5 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	3 mg/m³ (respirable particulate matter)
Saskatchewan	OEL STEL (mg/m³)	10 mg/m³
Saskatchewan	OEL TWA (mg/m³)	5 mg/m³
Yukon	OEL STEL (mg/m³)	10 mg/m³
Yukon	OEL TWA (mg/m³)	5 mg/m³
Tantalum (7440-25-7)		
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m³ (dust)
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m³ (dust)
USA IDLH	US IDLH (mg/m³)	2500 mg/m³ (dust)
Alberta	OEL TWA (mg/m³)	5 mg/m³ (dust)
British Columbia	OEL TWA (mg/m³)	5 mg/m <sup>3</sup>
New Brunswick	OEL TWA (mg/m³)	5 mg/m³ (dust)
Nunavut	OEL STEL (mg/m³)	10 mg/m³ (metal)
Nunavut	OEL TWA (mg/m³)	5 mg/m³ (metal)
Northwest Territories	OEL STEL (mg/m³)	10 mg/m³ (metal)
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³ (metal)
Québec	VEMP (mg/m³)	5 mg/m³ (dust)
Saskatchewan	OEL STEL (mg/m³)	10 mg/m³
Saskatchewan	OEL TWA (mg/m³)	5 mg/m³
Yukon	OEL STEL (mg/m³)	10 mg/m³
Yukon	OEL TWA (mg/m³)	5 mg/m³
Silicon (7440-21-3)		
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
	, ,, ,	5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
		5 mg/m³ (respirable dust)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
		3 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	10 mg/m <sup>3</sup>
Nunavut	OEL STEL (mg/m³)	20 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m³)	10 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m³)	20 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m³)	10 mg/m <sup>3</sup>
Québec	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline
		silica-total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m³)	10 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m³)	20 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m³

08/28/2018 EN (English US) 9/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Yttrium (7440-65-5)		
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³
USA IDLH	US IDLH (mg/m³)	500 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m³)	1 mg/m³
British Columbia	OEL TWA (mg/m³)	1 mg/m³
Manitoba	OEL TWA (mg/m³)	1 mg/m³
New Brunswick	OEL TWA (mg/m³)	1 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³
Nunavut	OEL STEL (mg/m³)	3 mg/m³
Nunavut	OEL TWA (mg/m³)	1 mg/m³
Northwest Territories	OEL STEL (mg/m³)	3 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m³)	1 mg/m³
Ontario	OEL TWA (mg/m³)	1 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³
Québec	VEMP (mg/m³)	1 mg/m³
Saskatchewan	OEL STEL (mg/m³)	3 mg/m³
Saskatchewan	OEL TWA (mg/m³)	1 mg/m³
Yukon	OEL STEL (mg/m³)	3 mg/m³
Yukon	OEL TWA (mg/m³)	1 mg/m³

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountain capability should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. In powdered form: Avoid dust production. Take precautionary measures against static discharges. Use explosion-proof equipment.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Evaporation Rate** 







Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Impermeable protective gloves.

**Eye and Face Protection:** Chemical safety goggles. Welders should wear goggles or safety glasses with sideshields that comply with ANSI Z87.1 under welding helmets and always wear goggles or other suitable eye protection when gas welding or oxygen cutting.

Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection:** Fumes and dust: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Thermal Hazard Protection: When working with hot material, use suitable thermally protective clothing.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on Basic Physical and Chemical Properties

Physical State: SolidAppearance: Gray; MetallicOdor: OdorlessOdor Threshold: Not availablepH: Not available

**Melting Point** : 1316 - 1538 °C (2400.8 - 2800.4 °F)

Freezing Point : Not available
Boiling Point : Not available
Flash Point : Not available

08/28/2018 EN (English US) 10/17

Not available

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available Not available **Vapor Pressure** Relative Vapor Density at 20°C Not available **Relative Density** Not available

Specific Gravity : ~8

Solubility: Water: InsolublePartition Coefficient: N-Octanol/Water: Not availableViscosity: Not available

## **SECTION 10: STABILITY AND REACTIVITY**

- **10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability: Stable under recommended handling and storage conditions (see Section 7).
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Dust, chips, or ribbons can be ignited more easily, by an ignition source, by improper machining, or by spontaneous combustion if finely divided and damp.
- **10.5. Incompatible Materials:** Oxidizers. Acids. Bases. Mineral acids. Corrosive substances in contact with metals may produce flammable hydrogen gas.
- **10.6.** Hazardous Decomposition Products: None expected under normal conditions of use.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Oral: Not classified.
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not classified
Eye Damage/Irritation: Not classified

**Respiratory or Skin Sensitization:** Not classified. May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified **Carcinogenicity:** May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

**Symptoms/Injuries After Inhalation:** During processing, the most significant route of exposure is by the inhalation (breathing) of fumes. If fumes are inhaled, they can cause a condition commonly known as metal fume fever with symptoms which resemble influenza; Symptoms may be delayed 4-12 hours and begin with a sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms may include upper respiratory tract irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalized feeling of malaise. Fever, chills, muscular pain, mild to severe headache, nausea, occasional vomiting, exaggerated mental activity, profuse sweating, excessive urination, diarrhea and prostration may also occur.

**Symptoms/Injuries After Skin Contact:** Dust may cause irritation in skin folds or by contact in combination with tight clothing. Contact with hot, molten metal will cause thermal burns. Removal of solidified molten material from skin requires medical assistance.

**Symptoms/Injuries After Eye Contact:** Dust generated from material cutting may cause a slight irritation. Slivers may be generated, which could cause mechanical irritation or injure the eye. Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Symptoms/Injuries After Ingestion: If large amounts are ingested: Gastrointestinal irritation.

**Chronic Symptoms:** May cause cancer. Suspected of damaging fertility or the unborn child. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Inhalation of iron oxide fumes

08/28/2018 EN (English US) 11/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

undergoing decomposition may cause irritation and flu-like symptoms, otherwise iron oxide is not hazardous. Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion. Copper: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. Molybdenum: Chronic exposure to molybdenum compounds is suspected of causing cancer. Compounds are also known to cause irritation to the skin, eyes, and respiratory tract. Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Chronic exposure to excessive manganese levels can lead to a variety of psychiatric and motor disturbances, termed manganism. Repeated exposure to tantalum alloys may cause fibrosis, chronic rhinitis and "hard metal pneumoconiosis". Silicon: Can cause chronic bronchitis and narrowing of the airways.

# 11.2. Information on Toxicological Effects - Ingredient(s) LD50 and LC50 Data:

Nickel (7440-02-0)	
LD50 Oral Rat	> 9000 mg/kg
Iron (7439-89-6)	
LD50 Oral Rat	98.6 g/kg
Chromium (7440-47-3)	·
LD50 Oral Rat	> 5000 mg/kg
LC50 Inhalation Rat	> 5.41 mg/l/4h
Cobalt (7440-48-4)	
LD50 Oral Rat	215.9 - 1140 mg/kg
LC50 Inhalation Rat	> 10 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	< 0.05 mg/l/4h
ATE US/CA (dust, mist)	0.01 mg/l/4h
Molybdenum (7439-98-7)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
LC50 Inhalation Rat	> 3.92 mg/l/4h
Manganese (7439-96-5)	
LD50 Oral Rat	> 2000 mg/kg
LC50 Inhalation Rat	> 5.14 mg/l/4h
Niobium (7440-03-1)	
LD50 Oral Rat	> 10 g/kg
Tantalum (7440-25-7)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Silicon (7440-21-3)	
LD50 Oral Rat	3160 mg/kg
Nickel (7440-02-0)	
IARC Group	2B
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Chromium (7440-47-3)	
IARC Group	3
Cobalt (7440-48-4)	
IARC Group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human
	Carcinogen.

08/28/2018 EN (English US) 12/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

**Ecology - General:** This product contains components that are environmentally hazardous and small chips and dust from processing may be toxic to aquatic life.

Nickel (7440-02-0)	
LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	15.3 mg/l
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Cobalt (7440-48-4)	
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
Manganese (7439-96-5)	
NOEC Chronic Fish	3.6 mg/l (Exposure time: 96h; Species: Oncorhynchus mykiss)

#### 12.2. Persistence and Degradability

Nickel Alloys	
Persistence and Degradability	Not readily biodegradable.
Copper (7440-50-8)	
Persistence and Degradability	Not readily biodegradable.

#### 12.3. Bioaccumulative Potential

Cobalt (7440-48-4)	
BCF Fish 1	(no bioaccumulation)

#### 12.4. Mobility in Soil

Not available

#### 12.5. Other Adverse Effects

Other Information: Avoid unnecessary release into the environment.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** Recycle where possible and/or dispose of spent material such as metals and metal-bearing waste and submerged arc welding (SAW) flux/slag appropriately.

#### **SECTION 14: TRANSPORT INFORMATION**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

**14.1. In Accordance with DOT** Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

14.4. In Accordance with TDG Not regulated for transport

### **SECTION 15: REGULATORY INFORMATION**

## 15.1. US Federal Regulations

Nickel Alloys	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
	Immediate (acute) health hazard
Nickel (7440-02-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb (only applicable if particles are < 100 $\mu$ m)
SARA Section 313 - Emission Reporting	0.1 %

08/28/2018 EN (English US) 13/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Iron (7439-89-6)	es And Regulations And According 10 The Hazardous Products Regulation (February 11, 2015).
Listed on the United States TSCA (Toxic Substances Co	entral Act inventory
	ntroi Act) inventory
Chromium (7440-47-3)	atast Ast Sansatan
Listed on the United States TSCA (Toxic Substances Co	· · · · ·
Subject to reporting requirements of United States SA CERCLA RQ	5000 lb no reporting of releases of this hazardous substance is
CERCLA RQ	required if the diameter of the pieces of the solid metal released is
	>100 μm
SARA Section 313 - Emission Reporting	1 %
Copper (7440-50-8)	
Listed on the United States TSCA (Toxic Substances Co	entral Act) inventory
Subject to reporting requirements of United States SAI	, ,
CERCLA RQ	5000 lb no reporting of releases of this hazardous substance is
	required if the diameter of the pieces of the solid metal released is
	>100 μm
SARA Section 313 - Emission Reporting	1%
Cobalt (7440-48-4)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Subject to reporting requirements of United States SA	
SARA Section 313 - Emission Reporting	0.1 %
Molybdenum (7439-98-7)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Aluminum (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Subject to reporting requirements of United States SA	RA Section 313
SARA Section 313 - Emission Reporting	1 % (dust or fume only)
Manganese (7439-96-5)	
Listed on the United States TSCA (Toxic Substances Co	
Subject to reporting requirements of United States SA	RA Section 313
SARA Section 313 - Emission Reporting	1%
Niobium (7440-03-1)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Tungsten (7440-33-7)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Titanium (7440-32-6)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Tantalum (7440-25-7)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Silicon (7440-21-3)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
Yttrium (7440-65-5)	
Listed on the United States TSCA (Toxic Substances Co	ntrol Act) inventory
15.2. US State Regulations	

## 15.2. US State Regulations

Nickel Alloys	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.

# **California Proposition 65**

 $\triangle$ 

This product can expose you to Nickel, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.) Carcinogenicity Developmental Female Reproductive Male Reproductive	
---	--

08/28/2018 EN (English US) 14/17

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		Toxicity	Toxicity	Toxicity
Nickel (7440-02-0)	Х			
Cobalt (7440-48-4)	Х			

#### Nickel (7440-02-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

#### Chromium (7440-47-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

## Copper (7440-50-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

#### Cobalt (7440-48-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

#### Molybdenum (7439-98-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

## Aluminum (7429-90-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

#### Manganese (7439-96-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

## Tungsten (7440-33-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

#### Titanium (7440-32-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

#### Tantalum (7440-25-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

# Silicon (7440-21-3)

U.S. - Massachusetts - Right To Know List

08/28/2018 EN (English US) 15/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

# Yttrium (7440-65-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

#### 15.3. Canadian Regulations

#### Nickel (7440-02-0)

Listed on the Canadian DSL (Domestic Substances List)

#### Iron (7439-89-6)

Listed on the Canadian DSL (Domestic Substances List)

#### Chromium (7440-47-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Copper (7440-50-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Cobalt (7440-48-4)

Listed on the Canadian DSL (Domestic Substances List)

#### Molvbdenum (7439-98-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Aluminum (7429-90-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Manganese (7439-96-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Niobium (7440-03-1)

Listed on the Canadian DSL (Domestic Substances List)

#### Tungsten (7440-33-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Titanium (7440-32-6)

Listed on the Canadian DSL (Domestic Substances List)

#### Tantalum (7440-25-7)

Listed on the Canadian DSL (Domestic Substances List)

#### Silicon (7440-21-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Yttrium (7440-65-5)

Listed on the Canadian DSL (Domestic Substances List)

# SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest** 

Revision

: 08/28/2018

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

#### **GHS Full Text Phrases:**

Acute Tox. 1 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 1
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Carc. 1B	Carcinogenicity Category 1B

08/28/2018 EN (English US) 16/17

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Repr. 2	Reproductive toxicity Category 2
Resp. Sens. 1B	Respiratory sensitization, Category 1B
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

08/28/2018 EN (English US) 17/17